

DASH Y62 PATROL SOFT LUGGAGE SHELF INSTALLATION INSTRUCTIONS



Contents:

- 1 x Soft Luggage Shelf
- 2 x Handle Mounting Brackets
- 1 x Head Board Panel
- 1 x Centre Divider
- 2 x Headrest Brackets & Spacers
- Hardware Set

Tools required

- 10mm socket
- 4mm Allen key (Not Included)



1. Remove third row roof grab handles. Fit both handle mounting brackets using bolts and washers in bag "A" and tighten.



2. On a soft surface fit head board to top of luggage shelf using 4 bolts and washers from bag "B". Fold up second row seats and slide luggage shelf into the handle mounting brackets. Align holes in handle mounting brackets, fit bolts and washers from bag "B" and tighten. Take care with hood lining and trim.

DASH Y62 PATROL SOFT LUGGAGE SHELF INSTALLATION INSTRUCTIONS



3. Fit center divider panel and bolt up with remaining bolts and washers from bag "B". Fit head rest brackets as shown and fit bolts, washers and nuts from bag "C" but don't tighten. Return seats into position but remove both outer head rests. Align brackets and spacers and re-insert head rests. Hold brackets in position and tighten.



Important Notes

- This Soft Luggage Shelf is only to be used in a 5 seater vehicle configuration.
- 3rd Row Seats are NOT to be used in conjunction with this product.
- If reinstalling / deploying 3rd row seats, this product must be completely removed from the vehicle.
- Maximum recommended payload is 10Kg, consisting of soft/light weight items.
- Second Row Seat Position Limited to Upright Position.
- Divider must be used with shelf as it provides support and stability to the system.
- **This product has not been tested to Australian Standards. It is not intended to be a 'Cargo Barrier' as defined by the Standard. It is designed to contain soft / light luggage & pets in your boot, under normal driving and braking conditions.**